


► PiXtend® V2 -S- Pi 4 & PiXtend® V2 -S-



PiXtend® V2 -S- Pi 4 & PiXtend® V2 -S- FAST, RELIABLE AND CONNECTION FRIENDLY

PiXtend® is a programmable logic controller based on the high-performing Raspberry Pi single-board computer. It is available in two variants, with the RPi 3 B+ Broadcom BCM 2837B0 and new with the RPi 4 B Broadcom BCM2711, the most powerful processor of the Raspberry Pi Foundation

The modules can be expanded with the PiXtend® eIO, an I/O system for digital and analog sensors and actuators that can be connected via Modbus. Other devices, controllers and computer system are easily connected via serial standard interfaces (RS232, Ethernet and WiFi). All these robust interfaces comply with the PLC standard (IEC 61131-2).

The PiXtend® controller can be programmed in common programming languages such as C or Python and is suitable for use with the CODESYS® SoftPLC. An integrated CODESYS® web visualization tool is available for displaying your control elements, diagrams and graphics on tablet or PC.

► FEATURES

- Retain memory for data back up
- Industrial outputs, High-Side switches with separate feed and all-round protection
- Use Node-RED to turn PiXtend® V2 into an edge device, data flows can be linked graphically and configured as required
- PiXtend® V2 Pi 4 housing with passive heat sink

► CUSTOMER BENEFITS

- Easy Design-In thanks to connection planner, 3D models and detailed manuals
- Quad PWM for actuating drives and model servos, without costly add-on modules
- Perfect connections, high-grade clamps, optional plug-in version

► APPLICATIONS

- Mechanical engineering controller
- Plant engineering controller

► TECHNICAL DATA


FUNCTION	PIXTEND® V2 -S- PI 4	PIXTEND® V2 -S-
CPU	Broadcom BCM 2711, Raspberry Pi 4 Model B	Broadcom BCM 2837B0, Raspberry Pi 3 Model B+
HARDWARE		
Power supply	24 V DC ±20 %	
Retain-/Remanence memory	32 Bytes Flash EEPROM	
Real Time Clock (RTC)	With battery buffering	
Temperature- and Air Humidity Sensors	Up to 4 DHT11, DHT22, AM2302	
RS232	1x	
RS485	Via USB-Dongle	
Digital inputs (DI)	8x 3,3 / 5 / 12 / 24 V	
Digital outputs (DO)	4x PNP 5 / 12 / 24 V, 0,5 A	
Analog voltage inputs (AI-U)	2x 0...5 V, 0...10 V, 10 Bit	
Analog voltage outputs (AO)	2x 0...10 V, 10 Bit	
Relais	4x, max. 230 V / 6 A	
PWM-/Servo outputs	2x 16 Bit, 2x 8 Bit resolution, 5 V	
GPIO	4x 5 V GPIO	
Interfaces and I/Os	Short circuit proof, supply with reverse polarity and overload protection (self-resetting safety device)	
Max. temperature range	0 °C...+50 °C	
Dimension – without housing	166,3 x 101,8 x 27 mm	
Top hat rail housing	Aluminium	
Supported RPI models	1 B+, 2 B, 3 B, 3 B+, 4 B	

PIXTEND® V2 CAN BE PROGRAMMED WITH THE FOLLOWING LANGUAGES

- CODESYS® V3 – Professional programming system for PLC programming according to IEC 61131-3
- C – Linux programming standard
- Python – Script language on the Raspberry Pi
- FHEM – Open source home automation system, control homes via web or app
- Node-RED – Graphical flow programming for the IoT age

► PiXtend® V2 -S- EXTENSION BOARD


PRODUCT NAME	ARTICLE NO.	OPTION
PiXtend® V2 -S- Extension Board	50199 004	Without Raspberry Pi



► PiXtend® V2 -S- ePLC® BASIC Pi 4

► PiXtend® V2 -S- ePLC® BASIC

PRODUCT NAME	ARTICLE NO.	OPTIONS
PiXtend® V2 -S- ePLC® Basic Pi 4	50199 020	Preinstalled SD-Card, Basis Image
PiXtend® V2 -S- ePLC® Basic Pi 4	50199 021	CODESYS® Image
PiXtend® V2 -S- ePLC® Basic	50199 005	Preinstalled SD-Card, Basis Image
PiXtend® V2 -S- ePLC® Basic	50199 013	CODESYS® Image




- Board basic version
- Open version
- Product with Raspberry Pi 4 B or product with Raspberry Pi 3 B+

► PiXtend® V2 -S- ePLC® PRO PI 4

► PiXtend® V2 -S- ePLC® PRO

PRODUCT NAME	ARTICLE NO.	OPTIONS
PiXtend® V2 -S- ePLC® Pro Pi 4	50199 024	Preinstalled SD-Card, Basis Image
PiXtend® V2 -S- ePLC® Pro Pi 4	50199 025	CODESYS® Image
PiXtend® V2 -S- ePLC® Pro	50199 005	Preinstalled SD-Card, Basis Image
PiXtend® V2 -S- ePLC® Pro	50199 013	CODESYS® Image



- Complete device Pro
- Top hat rail housing
- Brushed stainless steel
- Product with Raspberry Pi 4 B or Product with Raspberry Pi 3 B+

POSSIBILITIES START HERE



► ABOUT KONTRON ELECTRONICS

Kontron Electronics GmbH is a full-service provider in the field of electronics, development and manufacturing services. Our business portfolio includes proprietary and client-specific products, development and design services for complex electronics components, modules and systems, as well as production and assembly services for entire devices. The company is part of Kontron Europe and the technology corporation Kontron AG.

► YOUR CONTACT

Kontron Electronics GmbH

Max-Planck-Straße 6
72636 Frickenhausen, Germany
Tel.: +49 7022 4057-0
Fax: +49 7022 4057-22
info@kontron-electronics.de
www.kontron-electronics.de

► GLOBAL HEADQUARTERS

Kontron Europe GmbH

Gutenbergstraße 2
85737 Ismaning, Germany
Tel.: +49 821 4086-0
Fax: +49 821 4086-111
info@kontron.com
www.kontron.com